


机械参数:	
项目	标准
操作力	15±10gf
回复力	3.0gf Min.
行程	3.0mm Max.
过行程	1.2mm Min.
差程	0.9mm Max.
动作位置	9.1±1.6mm
自由位置	13.0 mm Max.



电性能:	
额定负载:	操作寿命:
2A 30VDC or 5A 125/250VAC (UL cUL)	6,000 次带负载
2A 30VDC or 5(2.5)A 125/250VAC (ENEC)	50,000 次带负载
2A 30VDC or 5(2.5)A 125/250VAC (CQC)	50,000 次带负载
绝缘电阻:	100MΩ Min.
抗电强度:	1000VAC(50~60HZ) - 非接触端子间
	1500VAC(50~60HZ) - 端子与接地(外壳)
	- 端子与非载流金属部件间
使用温度环境	-40°C~+125°C

材料清单	
胶座	热塑性塑料, UL94 V-0
胶盖	热塑性塑料, UL94 V-0
端子	铜合金, 镀银
按摩	热塑性塑料, UL94 V-0
触点	银合金
手柄	不锈钢

MASS PRODUCTION RELEASE

Project Ref:	S12系列微动开关	Tolerance Unless Otherwise Specified							
Part No:	S12AAF102-S01	~3	>3~10	>10~30	>30~80	>80~180	Angle		
Drawing No:	- - -	Eng Ver	A5	±0.20	±0.30	±0.40	±0.60	±0.80	±3°
Drafted by:	廖波	Date:	2012-01-31	Unit: mm	Size: A4	Scale:			
Checked by:	徐明杰	Date:	2012-01-31	THIRD ANGLE	TONELUCK				
Approved by:	徐明杰	Date:	2012-01-31	Switches & Control Solutions					