



SPECIFICATIONS	
设定压力点: 关闭压力	38±5Pa 负压
开启压力	65Pa Max 负压
最大工作压力:	3.5kPa(1/2PSI)
应用温度:	-25-88°C
接线端类型:	6.3X0.80 mm
负载:	UL353: 3A resistive, 120VAC 3A resistive, 30VDC 125 VA resistive, 120VAC CE: 1(0.5)A @ 125/250VAC
带电寿命:	100,000 CYCLES
机械寿命:	200,000 CYCLES
抗电强度:	1,000 VAC
绝缘阻抗:	50 MEGA OHM
触点材料:	Ag ALLOY
电路类型:	SPDT

**MASS PRODUCTION RELEASE**

@	2017-9-6	The Company Name Changed From GOLDTECH to TONELUCK	ECN=17007	A1
REV.	DATE	MODIFICATION	ECN NO.	PRIOR VERSION
Project Ref:	Air Pressure Switch		Tolerance Unless Otherwise Specified	
Part No:	PS160-B1110-B001		-3	>3-10
Drawing No:	- - -	Eng Ver	A2	±0.20 ±0.30 ±0.40 ±0.60 ±0.80 ±3°
Drafted by:	Owen Lee	Date:	2017-9-26	Unit: mm Size: A4 Scale:
Checked by:	Hugjian Wang	Date:	2017-9-26	THIRD ANGLE
Approved by:	Ray Xu	Date:	2017-9-26	<b>TONELUCK</b> Switches & Control Solutions